



Características de los perfiles UPE

Tél: +33 3 44 77 30 00



Tél: +33 3 44 77 30 00
stad@stad.fr

www.stad.fr



Características de los perfiles UPE

Perfiles U de alas paralelas

Tél: +33 3 44 77 30 00

Designación	G kg/m	Dimensiones						Valores estadísticos							
		H mm	B mm	Tw mm	Tf mm	R mm	I cm ²	Eje débil				Eje fuerte			
								ly cm ⁴	Wely cm ³	Wply cm ³	ly cm	Iz cm ⁴	Welz cm ³	Wplz cm ³	Iz cm
UPE 80	7,9	80,0	50	4,0	7,0	10	10,10	107	26,80	31,23	3,26	25,41	7,98	14,28	1,59
UPE 100	9,8	100,0	55	4,5	7,5	10	12,50	207	41,37	48,01	4,07	38,21	10,63	19,34	1,75
UPE 120	12,1	120,0	60	5,0	8,0	12	15,40	364	60,58	70,33	4,86	55,40	13,79	25,28	1,90
UPE 140	14,4	140,0	65	5,0	9,0	12	18,40	600	85,64	98,84	5,71	78,70	18,19	33,22	2,07
UPE 160	17,0	160,0	70	5,5	9,5	12	21,70	911	113,90	131,60	6,48	106,80	22,58	41,49	2,22
UPE 180	19,7	180,0	75	5,5	10,5	12	25,10	1.353	150,40	173,00	7,34	143,70	28,56	52,30	2,39
UPE 200	22,8	200,0	80	6,0	11,0	13	29,00	1.909	190,90	220,10	8,11	187,30	34,43	63,28	2,54
UPE 220	26,6	220,0	85	6,5	12,0	13	33,90	2.682	243,90	281,50	8,90	246,40	42,51	78,25	2,70
UPE 240	30,2	240,0	90	7,0	12,5	15	38,50	3.599	299,90	346,90	9,67	310,90	50,08	92,18	2,84
UPE 270	35,2	270,0	95	7,5	13,5	15	44,80	5.255	389,20	451,10	10,83	401,00	60,69	111,60	2,99
UPE 300	44,4	300,0	100	9,5	15,0	15	56,60	7.823	521,50	613,40	11,76	537,70	75,58	136,60	3,08
UPE 330	53,2	330,0	105	11,0	16,0	18	67,80	11.010	667,10	791,90	12,74	681,50	89,66	156,20	3,17
UPE 360	61,2	360,0	110	12,0	17,0	18	77,90	14.830	823,60	982,30	13,79	843,70	105,10	177,80	3,29

Tél: +33 3 44 77 30 00

stad@stad.fr

www.stad.fr



Características de los perfiles UPE

Perfiles U de alas paralelas

Tél: +33 3 44 77 30 00

Designación	G kg/m	Dimensiones						Valores estadísticos							
		H mm	B mm	Tw mm	Tf mm	R mm	I cm ²	Eje débil				Eje fuerte			
								ly cm ⁴	Wely cm ³	Wply cm ³	ly cm	Iz cm ⁴	Welz cm ³	Wplz cm ³	Iz cm
UPE 400	72,1	400,0	115	13,5	18,0	18	91,90	20.980	1.049,00	1.263,00	15,11	1.045,00	122,60	191,40	3,37

Tél: +33 3 44 77 30 00

stad@stad.fr

www.stad.fr