



Caratteristiche tecniche dei profili UC

Tel: +33 3 44 77 30 00



Tel: +33 3 44 77 30 00
stad@stad.fr

www.stad.fr



Caratteristiche tecniche dei profili UC

Tel: +33 3 44 77 30 00

Travi inglesi ad ali larghe

Denominazione	G kg/m	Dimensioni						I cm ²	Valori statici							
		H mm	B mm	Tw mm	Tf mm	R mm	Asso forte				Asso debole					
							Iy cm ⁴		Wely cm ³	Wply cm ³	Iy cm	Iz cm ⁴	Welz cm ³	Wplz cm ³	Iz cm	
UC 152 x 152 x 23	23,0	152,4	152	5,8	6,8	8	29,25	1.250	164,04	181,98	6,54	399,92	52,55	80,16	3,70	
UC 152 x 152 x 30	30,0	157,6	153	6,5	9,4	8	38,26	1.748	221,83	247,66	6,76	560,46	73,31	111,59	3,83	
UC 152 x 152 x 37	37,0	161,8	154	8,0	11,5	8	47,11	2.211	273,30	308,76	6,85	706,25	91,48	139,58	3,87	
UC 203 x 203 x 46	46,1	203,2	204	7,2	11,0	10	58,73	4.568	449,61	497,44	8,82	1.548,21	152,08	230,87	5,13	
UC 203 x 203 x 52	52,0	206,2	204	7,9	12,5	10	66,28	5.259	510,09	567,39	8,91	1.777,62	174,02	264,25	5,18	
UC 203 x 203 x 60	60,0	209,6	206	9,4	14,2	10	76,37	6.125	584,45	656,07	8,96	2.064,60	200,64	305,34	5,20	
UC 203 x 203 x 71	71,0	215,8	206	10,0	17,3	10	90,43	7.618	706,02	798,76	9,18	2.537,29	245,86	373,68	5,30	
UC 203 x 203 x 86	86,1	222,2	209	12,7	20,5	10	109,64	9.449	850,50	976,73	9,28	3.127,46	299,14	456,24	5,34	
UC 254 x 254 x 73	73,1	254,1	255	8,6	14,2	13	93,10	11.407	897,84	992,07	11,07	3.907,80	306,98	465,39	6,48	
UC 254 x 254 x 89	88,9	260,3	256	10,3	17,3	13	113,31	14.268	1.096,27	1.223,86	11,22	4.857,48	379,05	575,31	6,55	
UC 254 x 254 x 107	107,1	266,7	259	12,8	20,5	13	136,38	17.510	1.313,09	1.484,43	11,33	5.927,57	458,08	697,04	6,59	
UC 254 x 254 x 132	132,0	276,3	261	15,3	25,3	13	168,14	22.529	1.630,76	1.869,41	11,58	7.531,28	576,45	878,37	6,69	
UC 254 x 254 x 167	167,1	289,1	265	19,2	31,7	13	212,86	29.998	2.075,27	2.423,67	11,87	9.869,90	744,34	1.137,27	6,81	
UC 305 x 305 x 97	96,9	307,9	305	9,9	15,4	15	123,45	22.249	1.445,21	1.592,08	13,42	7.307,60	478,72	726,15	7,69	
UC 305 x 305 x 118	117,9	314,5	307	12,0	18,7	15	150,20	27.672	1.759,75	1.957,54	13,57	9.059,10	589,40	895,37	7,77	
UC 305 x 305 x 137	136,9	320,5	309	13,8	21,7	15	174,42	32.814	2.047,68	2.296,56	13,72	10.699,55	692,08	1.052,55	7,83	
UC 305 x 305 x 158	158,1	327,1	311	15,8	25,0	15	201,37	38.747	2.369,12	2.680,45	13,87	12.569,43	807,80	1.230,10	7,90	
UC 305 x 305 x 198	198,1	339,9	315	19,1	31,4	15	252,42	50.904	2.995,23	3.439,99	14,20	16.299,05	1.036,51	1.580,73	8,04	
UC 305 x 305 x 240	240,0	352,5	318	23,0	37,7	15	305,79	64.203	3.642,72	4.247,08	14,49	20.314,59	1.276,04	1.950,59	8,15	
UC 305 x 305 x 283	282,9	365,3	322	26,8	44,1	15	360,43	78.872	4.318,20	5.105,20	14,79	24.634,85	1.529,17	2.342,16	8,27	
UC 356 x 368 x 129	129,0	355,6	369	10,4	17,5	15	164,34	40.246	2.263,55	2.479,28	15,65	14.611,36	792,80	1.199,20	9,43	

Tel: +33 3 44 77 30 00

stad@stad.fr

www.stad.fr



Caratteristiche tecniche dei profili UC

Tel: +33 3 44 77 30 00

Travi inglesi ad ali larghe

Denominazione	G kg/m	Dimensioni						Valori statici							
		H mm	B mm	Tw mm	Tf mm	R mm	I cm ²	Asso forte				Asso debole			
								ly cm ⁴	Wely cm ³	Wply cm ³	Iy cm	Iz cm ⁴	Welz cm ³	Wplz cm ³	Iz cm
UC 356 x 368 x 153	152,9	362,0	371	12,3	20,7	15	194,80	48.589	2.684,48	2.964,74	15,79	17.553,17	947,54	1.434,77	9,49
UC 356 x 368 x 177	177,0	368,2	373	14,4	23,8	15	225,51	57.118	3.102,55	3.455,25	15,91	20.529,28	1.101,95	1.670,81	9,54
UC 356 x 368 x 202	201,9	374,6	375	16,5	27,0	15	257,22	66.261	3.537,69	3.971,75	16,05	23.688,41	1.264,39	1.919,53	9,60
UC 356 x 406 x 235	235,1	381,0	395	18,4	30,2	15	299,43	79.085	4.151,44	4.686,51	16,25	30.993,23	1.570,07	2.383,23	10,17
UC 356 x 406 x 287	287,1	393,6	399	22,6	36,5	15	365,71	99.875	5.074,95	5.812,49	16,53	38.677,35	1.938,71	2.949,27	10,28
UC 356 x 406 x 340	339,9	406,4	403	26,6	42,9	15	433,04	122.543	6.030,66	6.999,09	16,82	46.853,32	2.325,23	3.543,70	10,40
UC 356 x 406 x 393	393,0	419,0	407	30,6	49,2	15	500,58	146.618	6.998,47	8.222,45	17,11	55.367,34	2.720,75	4.153,73	10,52
UC 356 x 406 x 467	467,0	436,6	412	35,8	58,0	15	594,91	183.003	8.383,10	10.002,47	17,54	67.833,62	3.291,30	5.034,31	10,68
UC 356 x 406 x 551	551,0	455,6	419	42,1	67,5	15	701,93	226.938	9.962,16	12.076,27	17,98	82.670,53	3.950,80	6.057,96	10,85
UC 356 x 406 x 634	633,9	474,6	424	47,6	77,0	15	807,55	274.845	11.582,17	14.235,11	18,45	98.125,09	4.628,54	7.108,37	11,02

Tel: +33 3 44 77 30 00

stad@stad.fr

www.stad.fr